REV.A-3.21.2016

# **SDCR-200W Suggested Product Specification**

### Part 2 - Products

### 2.01 Manufacturer

- A. Acceptable Manufacturer: Protek Systems, Incorporated, 1250 Wallace Dr. Unit B, Delray Beach, FL 33444; Telephone: 800-598-2153, Fax: 561-395-4771, www.proteksystem.com
- B. Substitutions: Not permitted.
- C. Provide all crash rail and wall protection from a single source.

## 2.02 Welded Super Duty Crash Rails

- A. SDCR-200W Welded Super Duty Crash Rail by Protek Systems, Inc.
  - 1. Material: .050-inch aluminum cover with super duty polyurea coating and aluminum mounting brackets
  - 2. Profile: 1 1/2-inch depth x 5 1/2-inch height with center V-groove
  - 3. Finish: Full range of RAL colors available.
  - 4. Installation: Supplied in custom lengths with seamless welded ends
  - 5. Custom sizes and profiles available. Other thicknesses available.

### 2.03 Components

- A. CRBA-200 Standard Bracket
  - 1. Material: .063-inch grade 3003 mill finish aluminum
  - 2. Secures SDCR-200W cover to wall
  - 3. Spaced evenly not to exceed 32-inches on center
- B. SPLA-200 Splice Bracket
  - 1. Material: .063-inch grade 3003 mill finish aluminum
  - 2. Secures SDCR-200W cover to wall
  - 3. To be used as a splice where SDCR-200W covers meet
- C. Attachment Options
  - 1. Fasteners: Pre-drilled holes available. Fasteners by others.